



FACTSHEET

REF: 993549
994569

TILPASSING	D-XD
STØRRELSESUTVALG	39-48
FARGE	Brun
BOVENWERK	Nubuck / Oljet Nubuck
FØRING	Hydro-Tec® Antibakteriell
INNERSÅLE	Anti-penetrasjon / ESD
INNLEGGSSÅLE	Antibakteriell
TÅHETTE	Fiberglass / EN 12568:2010
BESKYTTENDE LAG	Vevd, ingen gjennomtrengning / EN 12568:2010
OVERLÆRETS KONSTRUKSJON	Strobel-konstruksjon (Randsydd)
MELLOMSÅLE	PU
YTTERSÅLE	GripForce® Easy Twist
YTRE TÅHETTE	Ingen
TYPE FESTE MEKANISME	Veter Grijs 135 CM
EUROPEISK STANDARD	EN ISO 20345:2011
ANTISTATISKE EGENSKAPER	ESD 0,1 - 35 M Ohm / NEN-EN-IEC 61340-5-1
ANTISKLI	SRC



DONOVAN

S3-Safetyshoe with sole plate for wet work

DONOVAN-D HGBR ESD
PU/PU S3 METAL FREE

Bransjer: Logistikk og transport,
Elektronikk, Bouw & techniek,
Produksjon, Natur og miljø,